Sight Glass O-Rings Kit

KIT INCLUDES

- Thin O-rings (Qty 2)
- Thick O-rings (Qty 2)

INSTALLATION INSTRUCTIONS

1. Due to micro-variances in handblown glass, your O-Ring Kit contains two different thicknesses of O-Rings.
2. We recommend that you install **ONE thin O-ring** in the *lower* groove in the Base Seat, and **ONE thick O-ring** in the *upper* groove in the Base Seat.
3. Next, rub a small amount of vegetable oil on the O-rings. This will help the glass tube glide into place.
4. Fully insert the Glass Tube **all the way** into the Base Seat. Make sure it is standing straight inside the Base Seat.

IMPORTANT TIPS

1. Since the Glass Tube is hand-blown glass, micro differences in diameter are inevitable. This means one end of the Glass Tube may insert into the Base Seat more easily than the other end. Test the fitment of both ends of the Glass Tube to determine which fitment you prefer. Do this *before* placing the sticker on the tube.
2. The measurement Sticker should never interfere with the O-Rings. In other words, cut the bottom of your sticker off if it is extending into the Base Seat. Exact placement of the sticker will vary based on the style and model of the pan you are using.
3. Use vegetable oil on the O-rings to help the glass glide into place.
4. If necessary for your particular glass, you may use TWO thick O-rings. OR TWO thin O-rings. Choose the fitment that works best for your situation. However, using one of each is usually a good place to start!

Smoky Lake Maple Products, LLC
SmokyLakeMaple.com • (920) 202-4500 • 208 N 12th Street, Hilbert, WI 54129